

jc535 U.S. PTO  
09/03/99

jc525 U.S. PTO  
09/389557

[illegible]

With reference to the filing in the United States Patent and Trademark Office of an application for patent in the name(s) of:

Shigeyuki Sano, Hiroyuki Matsuyama, & Yuzo Murayama

entitled: CONTROL APPARATUS AND VIDEO EQUIPMENT

— Small entity status under 37 CFR 1.9(f) is claimed and the amounts shown in parentheses below have been employed.

The following are enclosed:

## X Specification

X 16 Claims(s) (including 4 independent claim(s))

\_\_\_ Preliminary Amendment

X Unsigned Oath or Declaration, Power of Attorney & Petition

X 5 Sheet(s) of Drawings

X Our check for **\$1,206.00** calculated as follows:

Basic Fee of \$760 (\$380) .....	\$ 760.00
----------------------------------	-----------

6 Total Claims in excess of 20 at \$18 (\$9).....\$108.00

1 Ind. Claims in excess of 3 at \$78 (\$39).....\$78.00

<u>X</u>	Fee of \$260 (\$130) for Mult. Dep. Claim.....	\$260.00
----------	--	----------

Total Filing Fee ..... \$1,206.00

Assignment Recording Fee of \$40 ..... \$.00

X Certified copy of each of the following to substantiate the claim for priority:

<u>Application No.</u>	<u>Filing Date</u>	<u>Country</u>
P10-251332	September 4, 1998	JAPAN

X Please charge any additional fees required for the filing of this application and any other fees required during the pendency of this application or credit any overpayment to Deposit Account No. 03-3125. A duplicate copy of this letter is enclosed.

Respectfully submitted,

COOPER & DUNHAM, LLP

By: Jay H. Maioli  
Jay H. Maioli  
Reg. No. 27,213

599P1015

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application for Letters Patent

TITLE: CONTROL APPARATUS AND VIDEO EQUIPMENT

INVENTOR(S): SHIGEYUKI SANO  
HIROYUKI MATSUYAMA  
YUZO MURAYAMA

## CONTROL APPARATUS AND VIDEO EQUIPMENT

### BACKGROUND OF THE INVENTION

#### Field of the Invention

The present invention relates to a control apparatus and a video equipment suitable for use in, for example, displaying a sub screen as a second image together with a main screen as a first image on a display screen. More particularly, this invention makes it possible to smoothly control the displayed position of, for example, the second image or the like.

#### Description of the Related Art

Control apparatuses have been materialized, wherein, for example, when an equipment is controlled by handling a key, if the same key is activated continuously, a shift of control is accelerated so that a desired control will be executed smoothly. In the apparatuses, when a key is activated intermittently, the control is changed or shifted little by little. When the same key is activated continuously, the change or shift is accelerated. Thus, either of fine adjustment and smooth control can be carried out.

In the above control apparatuses, if the control direction is two-dimensional or higher dimensional, for example, two keys may be presumably used to carry out the control. In this case, when the two keys are activated alternately, the key operation is not continuous but intermittent. Control is

shifted little by little. It therefore takes too much time to carry out a desired control. Consequently, actions are not made smoothly.

By the way, a video equipment has been materialized, wherein a sub- screen regarded as a second image can be displayed together with a main screen regarded as a first image on a display screen, for example. In such a video equipment, the sub screen is displayed at one of four corners of the display screen, for example. The displayed position of the sub screen is thus limited. In the conventional equipment, therefore, there is a fear that at whichever of the corners the sub screen is displayed, an essential part of the main screen may be hidden behind the sub screen.

#### SUMMARY OF THE INVENTION

According to a first means of the present invention, the similarity and/or non-similarity of actions made by a plurality of command means is judged, so that even when the command means are activated alternately, if the similarity is judged, a response time is increased or decreased. According to this means, even if the control direction is two-dimensional or higher dimensional, actions can be made smoothly.

According to a second means of the present invention, a second image is displayed at any position on a display screen according to an action made by any command means. According to this means, the drawback that an essential part of a main screen

is hidden behind a sub screen can be overcome.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram showing the configuration of an example of a television image receiver to which a control apparatus, a video equipment and a control apparatus in accordance with the present invention are adapted;

FIG. 2 is a structural diagram showing the arrangement of operation buttons and a joystick serving as a plurality of command means;

FIG. 3A to FIG. 3C are each an explanatory diagram used to explain actions made according to a first embodiment;

FIG. 4 is a flowchart explaining the actions of the first embodiment;

FIG. 5A and FIG. 5B are each an explanatory diagrams used to explain actions made according to a second embodiment.

FIG. 6 is a flowchart explaining the actions of the second embodiment.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

According to a first embodiment of the present invention, there are provided a control apparatus having a plurality of command means and which controls an equipment according to respective actions made by the plurality of command means and a control method therefore. The control or method apparatus includes a means or a step for judging similarity and/or non-similarity of actions made by the plurality of

command means and a means or a step for determining a response time of control for respective actions made by the plurality of command means. When the plurality of command means are activated alternately, if the similarity of the actions is judged, the response time is increased or decreased.

According to a second embodiment of the present invention, there are provided a video equipment and a control method thereof capable of displaying a second image together with a first image on a display screen. The video equipment or control method includes a means or a step for arbitrarily controlling the displayed position of the second image, and displays the second image at an arbitrary position on the display screen according to an action made by any command means.

The present invention will be described with reference to the drawings. FIG. 1 is a block diagram showing the configuration of an example of a television set to which a control apparatus and a video equipment in accordance with the present invention are adapted. In this example, a main screen regarded as a first image and a sub screen regarded as a second image can be displayed on, for example, a display screen. Besides, the displayed position of the sub screen can be controlled arbitrarily.

Referring to FIG. 1, a video signal of the main screen regarded as the first image and displayed on the display screen is supplied to an input terminal 1. The video signal of the

main screen is supplied to a change-over switch 2 and switched to a video signal of a sub screen described later. A video signal output from the change-over switch 2 is supplied through an RGB drive circuit 3 to an image receiving tube 4 for depicting the aforesaid display screen.

Moreover, the video signal of the sub screen regarded as the second image is supplied to a sub screen signal production and control circuit 6 through an input terminal 5. A synchronizing or sync signal separated from the video signal of the main screen by a separation circuit 7, for example, is supplied to the production and control circuit 6. By this signal and a change at a reading speed at which data is read from an internal memory of the production and control circuit 6, the video signal of the sub screen is compressed to an arbitrary size and derived at an arbitrary timing on the display screen, whereby the video signal of the sub screen is produced.

The resultant video signal of the sub screen is supplied to the change-over switch 2. The production and control circuit 6 produces a switching signal whose timing corresponds to the timing of sweeping any position on the display screen. The change-over switch 2 is then changed over in response to the switching signal. Moreover the reading speed at which data is read from the internal memory of the production and control circuit 6 is changed. As a result, the sub screen of any size is composed at any position on the main screen.

Furthermore, a command signal entered using any command means, for example, a key scan or infrared rays (IR) emitted from a remote controller or the like is supplied to a microcomputer 9 through an input terminal 8. In the microcomputer 9, the command signal is supplied to a central processing unit (CPU) 10. A control signal defining the displayed position of the sub screen or the like is produced, and the control signal thus produced is supplied to the sub screen signal production and control circuit 6. Thus, the display position of the sub screen and others are controlled.

Command signals from a plurality of command means as shown in FIG. 2 are supplied to the input terminal 8. That is, referring to FIG. 2A, command signals indicating respective directions are supplied from four operation buttons of Up, Down, Right, and Left buttons. Also, referring to FIG. 2B, a so-called joystick is used to supply command signals indicating eight directions shown by arrows which are then supplied to the input terminal. The operation buttons or the joystick is located on an equipment body or a remote controller.

Assume that the sub screen is displayed at the right lower corner of the main screen as shown in FIG. 3A. In this state, when the operation button directed to the left is pressed as shown in FIG. 3B, the sub screen is moved leftward. When the operation button directed to the upward is pressed further, the sub screen is moved upward. Consequently, the sub screen is



displayed at the left upper corner of the main screen as shown in FIG. 3C. Thus, the sub screen can be displayed at any or arbitrary position on the main screen.

At this time, when, for example, the operation button directed to the left is pressed, the sub screen is moved slowly first. When the same operation button is kept pressing, the moving speed of the sub screen is increased gradually. This is intended to carry both a fine adjustment and a smooth control satisfactory. By contrast, in the conventional units, when the up-directed button is pressed next, the sub screen is moved slowly again. Thus, actions are made slowly but not smoothly.

Therefore, according to the aforesaid configuration, a means 11 for judging similarity and/or non-similarity of operation buttons and a means 12 for determining a response time of the control are included as a part of processing in the microcomputer 9. By the means, it is possible to control smoothly even for the above actions. FIG. 4 shows a flow according to which the microcomputer 9 processes a keyed-input, for example.

Referring to FIG. 4, when the processing is started, a keyed-input using the operation button or joystick mentioned above is detected at step S1. Data of the keyed-input is checked at step S2. It is judged at step S3 whether the keyed-input is the same as the previous input. At step S4, it is

judged whether the keyed-input is of the same kind as the previous input. An effective rate of the control is adjusted at step S5. The effective process of control is then executed at step S6. Then keyed-input processing is then terminated.

During the processing, if it is judged at step S3 that the keyed-input is the same as the previous input, such an adjustment that the effective rate of the control is increased gradually is carried out at step S5. If it is judged at step S4 that the keyed-input is of the same kind as the previous input, such an adjustment that the effective rate is increased gradually is performed. By contrast, if it is not judged at step S3 and S4 that the keyed-input is the same as or of the same kind as the previous input, such an adjustment that the effective rate of the control is returned to the initial value is carried out.

In other words, when the means 11 for judging the similarity and/or non-similarity of the operation buttons judges the similarity of the operation buttons, the means 12 for determining the response time of the control judges that the same operation button has been activated, and increases or decreases the response time. When the up-directed button is pressed after the left-directed button mentioned above is pressed, movement is kept accelerated, while actions are thus made smoothly.

Judging of the similarity and/or non-similarity of the

operation buttons is conducted, on the basis of a table listing combinations of similarities stored in, for example, a read-only memory (ROM) 13 or the like, by comparison of keyed-input data with immediately preceding keyed-input data stored in, for example, a random-access memory (RAM) 14 by means of the judging means 11.

In the foregoing control apparatus or equipment, the similarity and/or non-similarity of actions made by a plurality of command means is judged, and even when the command means are activated alternately, if the similarity is judged, the response time is increased or decreased. Therefore, even when the control direction is two-dimensional or higher dimensional, the actions can be made smoothly.

In the conventional apparatuses or equipments, there is a fear that when the control direction is two-dimensional or higher dimensional, the actions may not be made smoothly. According to the present invention, this drawback can be overcome readily.

An object to be controlled by the aforesaid apparatus or equipment is not limited to the displayed position of the sub screen on the main screen. The aforesaid unit or equipment can be employed in controlling the position of a cursor or a pointer. Moreover, the present invention is not limited to control of a position on the display screen. The present invention may be employed in setting a listening position for a

four-channel acoustic system or in controlling a hue and saturation or the like two-dimensionally or higher dimensionally.

In the foregoing apparatus or equipment, the sub screen can be, as shown in, for example, FIG. 5, moved to any position on the display screen by using the operation buttons or joystick. That is, FIG. 6 shows a flow according to which the microcomputer 9 sets the position of the sub screen.

Referring to FIG. 6, when the processing is started, keyed-input data is decoded at step S7. Keyed-input data is acquired at every interval of the aforesaid response time, for example. At step S8, keyed-input data is added up at every direction to thereby calculate the position of the sub screen. The position of the sub screen is set at the calculated position at step S9. Then, the sub screen position setting process is terminated.

In the aforesaid unit or equipment, a second image is displayed at any position on the display screen according to an action made by any command means. As a result, the drawback that an essential part of the main screen is hidden behind the sub screen can be overcome.

At the time of moving the position of the sub screen, by judging the similarity of the operation buttons, it is possible to carry out the actions smoothly.

In the foregoing unit or equipment, the displayed

position of the sub screen is not limited to the inside of the main screen as shown in FIG. 5A, but the sub screen may be, as shown in FIG. 5B, set outside an effective screen area of the display screen.

Furthermore, information of the set displayed position may be recorded and held in, for example, 14 random-access memory (RAM) 14. For example, even after the apparatus or equipment is left unused for some time, when it is reused, the sub screen or the like can be displayed at the previous displayed position.

As for the sub screen regarded as the second image, not only a picture represented by a video signal such as a picture to be broadcast or the like but also a menu screen used to set the apparatus or equipment and so on can be displayed. Moreover, a plurality of sub screens may be displayed.

According to the first embodiment of the present invention, there are provided the control apparatus and the control method having a plurality of command means and controlling the equipment according to actions made by the plurality of command means. The control apparatus or control method includes the means or the step for judging the similarity and/or non-similarity of the respective actions to be made by the plurality of command means, and the means or the step for determining a response time of control in response to each action made by each of the plurality of command means. When the

plurality of command means are activated alternately, if the similarity thereof is judged, the response time is increased or decreased. Thus, even when the control direction is two-dimensional or higher dimensional, the actions can be made smoothly.

According to the second embodiment of the present invention, there are provided the video equipment control apparatus and the control method which are capable of displaying a second image together with a first image on a display screen and which include the means or the step for arbitrarily controlling the displayed position of the second image. The second image is displayed at any position on the display screen according to an action made by any command means, whereby the drawback that, for example, an essential part of a main screen is hidden behind a sub screen and so on can thus be overcome.

Having described preferred embodiments of the present invention with reference to the accompanying drawings, it is to be understood that the present invention is not limited to the above-mentioned embodiments and that various changes and modifications can be effected therein by one skilled in the art without departing from the spirit or scope of the present invention as defined in the appended claims.

What is claimed is:

1. A control apparatus having a plurality of command means, and controlling an equipment according to each of actions made by said plurality of command means,

the control apparatus characterized by comprising:

a means for judging similarity and/or non-similarity of each of actions made by said plurality of command means; and

a means for determining a response time of said control in response to each of the actions made by said plurality of command means,

wherein when said plurality of command means are activated alternately, if said similarity is judged, said response time is increased or decreased.

2. A control apparatus according to claim 1,

wherein the control is such a control for a second image when the second image is displayed together with a first image on a display screen,

when a displayed position of said second image is controlled according to each of the actions made by said plurality of command means.

3. In a Video equipment capable of displaying a second image together with a first image on a display screen,

the video equipment characterized by comprising:

a means for controlling a displayed position of said second image arbitrarily,

wherein said second image is displayed at an arbitrary position on said display screen according to an action made by an arbitrary command means.

4. A video equipment according to claim 3,  
wherein said command means consists of a plurality of command means,

wherein there are provided,

a means for judging similarity and/or non-similarity of actions made by said plurality of command means, and

a means for determining a response of said control in response to each of the actions made by said plurality of command means,

when a displayed position of said second image is controlled according to an action made by each of the command means, and

when said plurality of command means is activated alternately, if the similarity of actions is judged, said response time is increased or decreased.

5. A video equipment according to claim 3,  
wherein the display position of said second image may be set outside an effective area of said display screen.

6. A video equipment according to any of claim 3 or 5,  
wherein there is provided a means for recording and holding information of the set displayed position of said second image.

7. A control apparatus according to any of claim 2, 3,



5 or 6,

wherein the control of said equipment is a control of a cursor.

8. A control apparatus according to any of claim 2, 3, 5, or 6,

wherein the control of said equipment is a control of a pointer.

9. In a control method having a plurality of command means, and controlling an equipment according to each of actions made by said plurality of command means,

the control method characterized by comprising:

a step for judging similarity and/or non-similarity of each of actions made by said plurality of command means; and

a step for determining a response time of said control in response to each of the actions made by said plurality of command means,

wherein when said plurality of command means are activated alternately, if said similarity is judged, said response time is increased or decreased.

10. A control method according to claim 9,

wherein the control of said equipment is such a control for a second image when the second image is displayed together with a first image on a display screen of the video equipment,

when a displayed position of said second image is controlled according to each of the actions made by said

plurality of command means.

11. In a control method of a Video equipment which is capable of displaying a second image together with a first image on a display screen,

the control method of a video equipment characterized by comprising:

a step for controlling a displayed position of said second image arbitrarily,

wherein said second image is displayed at an arbitrary position on said display screen according to an action made by an arbitrary command means.

12. A control method of a video equipment according to claim 11,

wherein said command means consists of a plurality of command means, and

there are comprised of,

a step for judging similarity and/or non-similarity of each of actions made by said plurality of command means, and

a step for determining a response of said control in response to each of the actions made by said plurality of command means,

when a displayed position of said second image is controlled according to an action made by each of the command means, and

when said plurality of command means is activated

alternately, if the similarity of actions is judged, said response time is increased or decreased.

13. A control method of a video equipment according to claim 11, wherein the displayed position of said second image may be set outside an effective area of said display screen.

14. A control method of a video equipment according to any of claim 11 or 13, wherein there is comprised of a step for recording and holding information of the set displayed position of said second image.

15. A control method according to any of claim 10, 11, 13 or 14,

wherein the control of said equipment is a control of a cursor.


16. A control method according to any of claim 10, 11, 13 or 14,

wherein the control of said equipment is a control of a pointer.


## ABSTRACT OF THE DISCLOSURE

A video signal of a main screen is supplied from an input terminal (1) through a change-over switch (2) and an RGB drive circuit (3) an image receiving tube (4). The video signal of a sub screen is also supplied to a sub screen signal production and control circuit (6) through an input terminal, compressed to an arbitrary size, and derived at an arbitrary positional timing to thereby produce the video signal of the sub screen. A command signal from a commanding means is further supplied to a microcomputer (9) through an input terminal (8). In the microcomputer 9, the command signal mentioned above is supplied to a central processing unit (CPU) (10). The central processing unit produces a control signal indicating the displayed position of the sub screen or the like. In a part of the processing, the similarity and/or non-similarity of operation buttons is judged and a response time of the control is determined, whereby the actions can be carried out smoothly.


**FIG. 1**




**FIG. 2A**




**FIG. 2B**



**FIG. 3A**



**FIG. 3B**



**FIG. 3C**






FIG. 4



**FIG. 5A**



**FIG. 5B**







FIG. 6



**7217/59652**

**As a below-named inventor, I hereby declare that:**

**I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:**

  X   is attached hereto.

\_\_\_\_\_ was filed on \_\_\_\_\_ as \_\_\_\_\_

Application Serial No. \_\_\_\_\_

and was amended on \_\_\_\_\_ (if applicable)

**I acknowledge the duty to disclose information of which I am aware which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, Section 1.56(a).**

**Prior Foreign Application(s)**

**Priority Claimed**

<u>Number</u>	<u>Country</u>	<u>Filing Date</u>	<u>Yes</u>	<u>No</u>
<u>P10-251332</u>	<u>Japan</u>	<u>September 4, 1998</u>	<u>X</u>	<u>      </u>

Declaration and Power of Attorney

Page 2

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States Application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, Section 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

<u>Application Serial No.</u>	<u>Filing Date</u>	<u>Status</u>
_____	_____	_____
_____	_____	_____

And I hereby appoint Jay H. Maioli, Reg. No. 27,213; Donald S. Dowden, Reg. No. 20,701; William E. Pelton, Reg. No. 25,702; Peter J. Phillips, Reg. No. 29,691; Gerald W. Griffin, Reg. No. 18,886; Ivan S. Kavrukov, Reg. No. 25,161; Christopher C. Dunham, Reg. No. 22,031; Norman H. Zivin, Reg. No. 25,385; John P. White, Reg. No. 28,678; and Robert D. Katz, Reg. No. 30,141; and each and all of them, all c/o Cooper & Dunham, 1185 Avenue of the Americas, New York, NY 10036 (Tel. (212) 278-0400), my attorneys, each with full power of substitution and revocation, to receive the patent, to transact all business in the Patent and Trademark Office connected therewith and to file any International Applications which are based thereon under the provisions of the Patent Cooperation Treaty.

Please address all communications, and direct all telephone calls, regarding this application to

**JAY H. MAIOLI**  
Cooper & Dunham LLP  
1185 Avenue of the Americas  
New York, New York 10036  
Tel. (212) 278-0400

Reg. No. 27,213

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or  
First joint inventor Shigeyuki Sano

Inventor's signature \_\_\_\_\_

Citizenship Japanese Date of Signature \_\_\_\_\_

Residence Kanagawa, Japan

Post Office Address c/o Sony Corporation, 7-35 Kitashinagawa, 6-chome

Shinagawa-ku, Tokyo 141, JAPAN

S99P1015US00

7217/59652

Full name of

Second joint inventor Hiroyuki Matsuyama

Inventor's signature \_\_\_\_\_

Citizenship Japanese

Date of Signature \_\_\_\_\_

Residence Tokyo, Japan

Post Office Address c/o Sony Corporation, 7-35 Kitashinagawa, 6-chome

Shinagawa-ku, Tokyo 141, JAPAN

Full name of

Third joint inventor Yuzo Murayama

Inventor's signature \_\_\_\_\_

Citizenship Japanese

Date of Signature \_\_\_\_\_

Residence Tokyo, Japan

Post Office Address c/o Sony Corporation, 7-35 Kitashinagawa, 6-chome

Shinagawa-ku, Tokyo 141, JAPAN